

Spring loaded safety crank Sifeku

- Without pawl.
- Silent
- Recoil proof
- Maintenance-free
- Enclosed housing
- Weather and temperature resistant.
- Braking effect at both ends.
- The load is held safely at every height, in the pushing and pulling direction.
- Approved by the TÜV as an independent crank.
- With folding handle.



Technical data spring loaded safety crank Sifeku

Model	EAN-No. 4025092*	Capacity kg	Length of crank mm	Square drive mm	Drive torque max. Nm
Sifeku 1,5	*562522	1500	250	14	60
Sifeku 3	*562522	3000	250	14	60
Sifeku 5	*562522	5000	250	14	60
Pfaff design					
Sifeku 1,5	*984041	1500	250	17	60
Sifeku 3	*984041	3000	250	17	60
Sifeku 5	*984041	5000	250	17	60

Crank with folding handle for model ZWW-L (only optional)

- Crank with collapsible handle, length of crank = 200 mm for ZWW-L 250 and 1000 EAN-No. 4025092 652025
- Crank with collapsible handle, length of crank = 250 mm for ZWW-L 500 EAN-No. 4025092 651882



Safety spring-lock with plug crank Sifespe

- Plug crank removable
- No ratchet pawls in use
- Silent
- Maintenance-free
- Housing
- Weather and temperature resistant
- Braking effect at both ends
- The load is held safely at every height
- Handle not folding

Arm length 250 mm

- Square drive 14 mm or 17 mm



INFO

For ordering the crank of the models STW-F, STW-V, STW-FvB, KHB and SCH-W it takes note to specify the manufacture year, capacity and the dimension of the square!

Safety spring-lock EAN-No. 4053981 022680

Plug crank EAN-No. 4053981 001968



Safety crank, zinc-plated Siku

- With one-sided braking effect.
- The load is held safely at every height.
- With folding handle.



Ratchet pawl kit, zinc-plated
for crank execution
Siku and Raku
P13 EAN-No. 4025092 655811
P14 EAN-No. 4053981 827698

Technical data safety crank Siku

Model	EAN-No. 4025092* 4053981**	Capacity kg	Length of crank mm	Square drive mm	Drive torque max. Nm
Siku 1,5	**022703	1500	200	14	60
Siku 3	*562553	3000	250	14	60
Siku 5	*562553	5000	250	14	60
Siku 10	*993036	10000	300	17	120

Pfaff design

Siku 1,5	*441469	1500	250	17	60
Siku 3	*441469	3000	250	17	60
Siku 5	*441469	5000	250	17	60



Safety ratchet crank, zinc-plated Raku

- Lifting or lowering movement adjustable by turning a lever.
- The load is held safely at every height.
- With folding handle.

Technical data safety ratchet crank Raku

Model	EAN-No. 4025092* 4053981**	Capacity kg	Length of crank mm	Square drive mm	Drive torque max. Nm
Raku 1,5	**022697	1500	200	14	60
Raku 3	*915649	3000	250	14	60
Raku 5	*915649	5000	250	14	60
Raku 10	*997492	10000	300	17	120

Pfaff design

Raku 1,5	*655743	1500	250	17	60
Raku 3	*655743	3000	250	17	60
Raku 5	*655743	5000	250	17	60